







Capsule System



Gran Gusto Tech





Power Boost



3 Way Pay

Atlante Evo 700 CapBean

Atlante Evo 700 CapBean is based on the Atlante platform, of which it maintains all the main characteristics; it is the latest Saeco technical development, using both coffee beans and capsules, of the LB type or Caffitaly System, to brew coffeebased drinks. Inside the machine there are a capsule search/ orientation rotor, a conveyor system and a dedicated brewing unit, for easy and effective capsule management. Thanks also to the 5 powder containers, the machine can brew a wide variety of drinks, like the systems designed for the medium-to-large size

We are partnered by the best coffee roasters: Lavazza, for OCS, Caffitaly, with a proprietary capsule, and Covim, that adopted an LB-

Accessories

- Independent water tank kit
- Mixer kit for tea replacement with soluble mixer
- · Hot water solenoid valve kit
- Memory key to copy and quickly transfer machine settings.
- USB key kit
- Eva-Dts kit
- Atlante Evo Master transformation kit

Main features

- Works with capsules of the LB type or Caffitaly System
- Loose capsule loadingBrewing unit with Gran Gusto System + Gran Gusto 6 grams kit (7 gr Espresso version)
- Gran Gusto hydraulics
- New silk-printed images for the upper and lower panels
- LED lighting system
- Generous container capacity
- Easy cleaning and maintenance thanks to the new Saeco Rotating Plate system
- Easily customizable backlit front panels
- · User-friendly interface with colour graphic LCD display and easy-toread and illuminated mechanical buttons
- Versatile dispensing area allowing cups with sizes up to 20 oz (592 ml)
- Possibility to install 3 payment systems on the door at the same time (Saeco 3 Way Pay)
- Accepts the most commonly used parallel and serial MDB, BDV and Executive (possible Master and Slave configurations) payment systems
- The machine is designed for easy use even by persons with disabilities

User interface

- Direct access 20-button keypad for beverage selection
- 2 preselection keys: +/-sugar and 2 settable keys (decaffeinated/ barley, no-cup and only-cup options)
- Colour graphic LCD display

Technical data

Atlante Evo 700 CapBean

recilinear data	7 telante = 10 7 00 Cappoan
Structural specifications	
Dimensions ($w \times h \times d$)	750 × 1830 × 865 mm
Weight	185 kg
Electrical specifications	
Power supply	230 V/50 Hz
Power consumption	2300 ₩
Water specifications	
Boiler	3
Espresso boiler	brass (600 cc)
Instant boiler	stainless steel (4.5 I)
Pre-heating boiler	stainless steel
Water connections	
Water connection	3/4" (I – 8 bar)
Water supply	standard: water supply
	optional: independent water tank kit
Independent water tank	2 tanks of 20 l
Other specifications	
Cups (h 70 mm)	700
Cups type ø	70 o 73 mm
Stirrers	550
Available stirrers	90 – 105 – 115 mm
Coffee bean container	I I
Capsule container	I I
Instant product container	5
Sugar container	I I
Number of selections	20
Number of preselections	2
Disc mixer	2
Spiral mixer	I I
Brewing unit	7 gr (Gran Gusto system) or 9 gr
Capsule brewing unit	yes
Canisters capacity	
Coffee beans	I x 3.5 kg
Capsules	300 LB-type or 280 Caffitaly system
Decaffeinated coffee	0.7 kg
Milk	1.3 kg
Chocolate	3.5 kg
Ginseng	2.5 kg
Tea	4 kg
Sugar	4.5 kg

Technical specifications

- Pre-galvanized and painted steel-sheet body
- Containers and tanks in food-contact approved resin
- Saeco Rotating Plate system
- Rielda lock
- Refill signal for water, coffee and cups
- Adjustable stirrer dispenser
- Electronically controlled boilers temperature
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area
- Illuminated keypad, logo and promotional images



- Removable cup-releasing device for easy cleaning and checking
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- · Simplified error reset
- Built-in utility outlet
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- Safety and anti-boiling thermostats for instant products
- CE and VDE approved



+
Atlante Evo 700 CapBean



+
Atlante Evo 700 CapBean